

WOW

YOUR WALLS WITH WALL PUTTY!



Mason Wall Putty

Cement Based Finishing Plaster



Extra fine finish



Interior and exterior applications



Available in white and grey



Commercial and residential uses

| Description | SKU code | Sales Unit | Weight | Bags per Pallet | Ean code |
|------------------|----------|------------|--------|-----------------|---------------|
| Wall Putty White | 31561 | Each | 20 kg | 100 bags | 6002761003218 |
| Wall Putty Grey | 31652 | Each | 20 kg | 100 bags | 6002761003225 |



Let's Get Started!



Add water

STEP 1

3 parts of powder with 1 part clean water (by volume).



Add dry mix

STEP 2

Mix 20 kg bag of powder with 8 - 8.5 litres of clean water.



Mixing time

STEP 3

Use an electric mixer at low speed for 3 minutes until you get a lump-free paste. Do not over-mix.



Rapid set

STEP 4

Leave the mix to stand for 2 minutes, then mix again for 1 minute.



Mixing time

STEP 5

Do not mix more Mason Wall Putty than you can use in 60 minutes.



Trowel application

STEP 6

Using a clean putty knife or trowel, apply plaster onto the wall using a "scrape on, scrape off" method to achieve the desired thickness.

Application Guide

- As a first coat, use a thickness layer of 0.5 - 1.5 mm.
- Leave enough time for the first coat to set and dry (30 - 120 minutes).
- Apply additional coats until a smooth surface is achieved. A total applied thickness should be 1.5 - 2.5 mm.
- Once the application is complete, allow the wall surface to be fully set and dry.
- To remove surface imperfections, lightly sand with fine grit (180 - 220) sanding paper.

