

Weber Acrylic Sealant

General Use



DESCRIPTION

A one-part, water-based acrylic sealant designed for sealing and filling gaps for indoor applications. It is flexible, fast-curing, paintable after 1 hour, and water-resistant once cured. The product delivers a smooth, professional finish and is suitable for use on a variety of surfaces.



Paintable



Can be sanded






Need an applicator gun

USES

Sealing around cornices, plasterboard, and ceiling gaps

- Window and door frames
- Hairline cracks
- Glass, wood, and metals
- Ceramic tiles and most plastics



ADVANTAGES

- This sealant is easy to apply, low in shrinkage, and resists cracking after curing
- It offers 100% joint movement capability and is sandable once cured
- It is paintable after 1 hour and cleans up with water before curing

COLOURS

WHITE

TYPICAL PHYSICAL PROPERTIES

Density	1.68 g/cm ³
Tack-free time	35 min
Sag	0 mm
Shore A Hardness	64
Curing depth (24h)	2 mm
Curing depth (7d)	5 mm
Elongation at break	240%
Tensile strength	0.36MPa

Acrylic Sealant

SURFACE PREPARATION

Surfaces must be clean and free of grease and old glue. Mask smooth surfaces to simplify cleanup.

BONDING/PRIMING

No primer required.

MIXING

No mixing needed. Ready to use straight from the tube.

COVERAGE

Dependent on joint size, approximate coverage is 7.7 m per 280 ml cartridge based on a 6 mm x 6 mm joint.

APPLICATION

- Cut the nozzle at an angle and apply the sealant using a caulking gun, pressing firmly to ensure good contact with the surface. Use masking tape on both sides of the joint to keep the edges neat and protect surrounding areas
- For better control, start applying the sealant while pulling the gun toward you
- Tool the joint within five minutes using a spatula dipped in mild soapy water
- Remove the masking tape right after tooling

PROTECTION ON COMPLETION

Ensure full cure before mechanical stress or painting. Not for food-contact or structural glazing.

APPLICATION TEMPERATURE

+5 °C to +45 °C

PACKAGING

280ml cartridge.

Other sizes may be available.

HANDLING AND STORAGE

Shelf life: 15 months in unopened packaging.

Storage: +5 °C to +27 °C, humidity 30-70%.

Don't return used material to the container.

HEALTH AND SAFETY

- Keep out of reach of children
- Read all safety instructions
- Refer to MSDS for full guidance

IMPORTANT NOTE

- Data may change
- Users must confirm suitability
- No liability for misuse

GUARANTEE

We agree that **Weber** products meet the product specifications and will be free from any defect. Any guarantee with regard to the performance of **Weber** products will be subject to its professional and practical application of **Weber** products in accordance with our instructions and specifications. However, we have no influence over specific site conditions and therefore, if in doubt, the user should first carry out sufficient tests to ensure that the product is suitable. In special cases, obtain advice. Should our product prove defective, we undertake to replace any defective material. This guarantee will fall away in the event of **Weber** products being contaminated by the addition of sand, cement or substance other than recommended by us.

TECHNICAL SERVICES

Weber has a team of experienced advisors available to provide technical support. Technical helpline: **0786181915** or <https://www.saint-gobain-africa.com/en/zimbabwe> .